

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

SECTION 1. IDENTIFICATION

Product name : Genetron® AZ-50 (R-507)

Number : 00000009882

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 800-522-8001
+1-973-455-6300(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : very faint sweet

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Storage:**
Protect from sunlight. Store in a well-ventilated place.Hazards not otherwise
classified: May cause frostbite.
May cause cardiac arrhythmia.
May cause eye and skin irritation.**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

: Mixture of 1,1,1-Trifluoroethane and Pentafluoroethane

Chemical nature

: Mixture

Chemical name	CAS-No.	Concentration
Pentafluoroethane	354-33-6	50.00 %
1,1,1-Trifluoroethane	420-46-2	50.00 %

SECTION 4. FIRST AID MEASURES

General advice

: First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

- Indication of immediate medical attention and special treatment needed, if necessary : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : The product is not flammable.
ASTM E-681
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during firefighting : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

reducing oxygen available for breathing.
Rapid evaporation of the liquid may cause frostbite.
Fire may cause evolution of:
Halogenated compounds
Hydrogen fluoride
Carbon oxides
Carbonyl halides

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.

Methods and materials for containment and cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Handle with care.
Avoid inhalation of vapour or mist.

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

Do not get in eyes, on skin, or on clothing.
 Wear personal protective equipment.
 Use only in well-ventilated areas.
 Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
 Follow all standard safety precautions for handling and use of compressed gas cylinders.
 Use authorized cylinders only.
 Protect cylinders from physical damage.
 Do not puncture or drop cylinders, expose them to open flame or excessive heat.
 Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
 Do not remove screw cap until immediately ready for use.
 Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.
 Can form a combustible mixture with air at pressures above atmospheric pressure.

Storage

Conditions for safe storage, including any incompatibilities : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
 Keep containers tightly closed in a dry, cool and well-ventilated place.
 Storage rooms must be properly ventilated.
 Ensure adequate ventilation, especially in confined areas.
 Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.
 Avoid contact with skin, eyes and clothing.
 Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.
 Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection : Wear as appropriate:
 Safety glasses with side-shields

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

- If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Hand protection : Leather gloves
In case of contact through splashing:
Protective gloves
Neoprene gloves
Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear cold insulating gloves/ face shield/ eye protection.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Pentafluoroethane	354-33-6	TWA : Time weighted average	4,900 mg/m ³ (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide

Pentafluoroethane	354-33-6	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
-------------------	----------	--------------------------------	-------------	--	---

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

1,1,1-Trifluoroethane	420-46-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1-Trifluoroethane	420-46-2	TWA : Time weighted average	3,400 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquefied gas
Color	: colourless
Odor	: very faint sweet
Odor threshold	: Note: no data available
pH	: Note: neutral
Freezing point	: Note: not determined
Boiling point/boiling range	: -46.7 °C
Flash point	: Note: Not applicable
Evaporation rate	: > 1 Method: Compared to CCl4.
Lower explosion limit	: Method: ASTM E-681 Note: None
Upper explosion limit	: Method: ASTM E-681 Note: None

000000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

Vapor pressure	:	10,611 hPa at 21.1 °C(70.0 °F) 25,289 hPa at 54.4 °C(129.9 °F)
Vapor density	:	3.43 Note: (Air = 1.0)
Density	:	1.07 g/cm ³ at 21.1 °C
Water solubility	:	1.5 g/l
Partition coefficient: n-octanol/water	:	log Pow: 1.48 Test substance: Ethane, pentafluoro- (HFC-125)
Ignition temperature	:	> 750 °C
Decomposition temperature	:	> 250 °C Note: To avoid thermal decomposition, do not overheat.
Viscosity, dynamic	:	Note: no data available
Viscosity, kinematic	:	Note: no data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature.

000000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

Some risk may be expected of corrosive and toxic decomposition products.
 Can form a combustible mixture with air at pressures above atmospheric pressure.
 Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials : Oxidizing agents
 Finely divided metal powders such as aluminum, magnesium, or zinc.

Hazardous decomposition products : Halogenated compounds
 Hydrogen fluoride
 Carbonyl halides
 Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

Pentafluoroethane : > 769000 ppm
 Exposure time: 4 h
 Species: Rat

1,1,1-Trifluoroethane : LC50: > 540000 ppm
 Exposure time: 4 h
 Species: Rat

LC50: > 106 mg/l
 Exposure time: 4 h
 Species: Rat

Sensitisation

Pentafluoroethane : Cardiac sensitization
 Species: dogs
 Note: No-observed-effect level
 75 000 ppm
 Lowest observed effect level
 100 000 ppm

1,1,1-Trifluoroethane : Cardiac sensitization
 Species: dogs
 Note: 1,1,1,2-tetrafluoroethane (HFC-134a): Cardiac

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

sensitisation threshold (dog): 80000 ppm.

Repeated dose toxicity
Pentafluoroethane: Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOEL: 50000 ppm
Subchronic toxicity

1,1,1-Trifluoroethane

: Species: Rat
Application Route: Inhalation
Exposure time: (90 d)
NOEL: 40000 ppm
Subchronic toxicityGenotoxicity in vitro
Pentafluoroethane: Test Method: Ames test
Result: negative

1,1,1-Trifluoroethane

: Test Method: Ames test
Result: negative: Cell type: Human lymphocytes
Result: negative: Cell type: Chinese Hamster Ovary Cells
Result: negative: Cell type: Human lymphocytes
Result: negativeGenotoxicity in vivo
1,1,1-Trifluoroethane: Species: Mouse
Cell type: Bone marrow
Application Route: Inhalation
Result: negativeTeratogenicity
Pentafluoroethane: Species: Rabbit
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm

000000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

Note: Did not show teratogenic effects in animal experiments.

Species: Rat

Application Route: Inhalation exposure

NOAEL, Teratog: 50,000 ppm

NOAEL, Maternal: 50,000 ppm

Note: Did not show teratogenic effects in animal experiments.

1,1,1-Trifluoroethane

: Species: Rat

Application Route: Inhalation exposure

NOAEL, Teratog: 40,000 ppm

NOAEL, Maternal: 40,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Species: Rabbit

Application Route: Inhalation exposure

NOAEL, Teratog: 40,000 ppm

NOAEL, Maternal: 40,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Further information

: Acute toxicity Ethane, pentafluoro- (HFC-125): Cardiac sensitisation threshold (dog): 75000 ppm. 1,1,1-trifluoroethane (HFC-143a): Cardiac sensitisation threshold (dog): >250000 ppm. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. Irritating to eyes and skin. Avoid skin contact with leaking liquid (danger of frostbite). May cause cardiac arrhythmia.

SECTION 12. ECOLOGICAL INFORMATION

Biodegradability

Pentafluoroethane

: Result: Not readily biodegradable.

Value: 5 %

Method: OECD 301 D

Further information on ecology

Additional ecological information

: Accumulation in aquatic organisms is unlikely. This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

SECTION 13. DISPOSAL CONSIDERATIONS

- Disposal methods : Observe all Federal, State, and Local Environmental regulations.
- Note : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

- DOT**
- | | | |
|----------------------|---|---|
| UN/ID No. | : | UN 3163 |
| Proper shipping name | : | LIQUEFIED GAS, N.O.S.
(Pentafluoroethane, 1,1,1-Trifluoroethane) |
| Class | : | 2.2 |
| Packing group | : | |
| Hazard Labels | : | 2.2 |
- IATA**
- | | | |
|--|---|---|
| UN/ID No. | : | UN 3163 |
| Description of the goods | : | LIQUEFIED GAS, N.O.S.
(Pentafluoroethane, 1,1,1-Trifluoroethane) |
| Class | : | 2.2 |
| Hazard Labels | : | 2.2 |
| Packing instruction (cargo aircraft) | : | 200 |
| Packing instruction (passenger aircraft) | : | 200 |
- IMDG**
- | | | |
|--------------------------|---|---|
| UN/ID No. | : | UN 3163 |
| Description of the goods | : | LIQUEFIED GAS, N.O.S.
(PENTAFLUOROETHANE, 1,1,1-TRIFLUOROETHANE) |
| Class | : | 2.2 |
| Hazard Labels | : | 2.2 |
| EmS Number | : | F-C, S-V |
| Marine pollutant | : | no |

SECTION 15. REGULATORY INFORMATION**Inventories**

00000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

- US. Toxic Substances Control Act : On TSCA Inventory
- Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory
- Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL
- Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory
- Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory
- Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory
- China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory
- NZIOC - New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

- SARA 302 Components** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313 Components** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
- SARA 311/312 Hazards** : Acute Health Hazard
Sudden Release of Pressure Hazard

000000009882

Version 2.7

Revision Date 05/08/2019

Print Date 05/17/2021

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 06/02/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group